

Product datasheet:

One-gang junction box for solid wood

Air-tight one-gang boxes, one-gang junction boxes, accessories

- for clamped attachment in solid wood from 10 mm thickness upwards
- not suitable for use with plasterboard or mineral fibreboard!
- With holding ring

One-gang junction box, air-tight, for cavity wall installation, cavity wall box, designed as a cavity wall device connection box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, air-tight design in accordance with DIN 18015-5, installation opening Ø 60 mm, installation opening Ø 68 mm, depth 65 mm, with clamping rib fastening for multi-layer wall structures in timber construction, with 4 screw domes, with 2 screw domes and 2 plus-minus device screws. 4 markings for electric cable or conduit entries up to max. Ø 25 mm using universal opening cutter (Art. no. 1085-80), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C



Certificates



Planning data

Article number:	9066-12
EAN:	4013456220515
Inner packing / Packaging quantity:	25 / 250
Price group:	121
Dimensions / Form	
Product depth:	65 mm
Drill/cut hole Ø:	68 mm
Connections / Entries	
For conduit Ø:	25 mm
Assembly / Installation	
Assembly type:	HW (drywall/lightweight construction)
Safety / Properties	
air tightness:	Yes
Approvals / Certifications	
VDE:	Yes