

Product datasheet:

One-gang box CEE, halogenfree

Air-tight one-gang boxes, one-gang junction boxes, accessories

- for use with 16A CEE equipment inserts
- With holding ring

Device box, for cavity wall installation.

Cavity wall box, designed as a cavity wall device box in accordance with DIN EN 60670/ VDE 0606 and DIN 49073, made of plastic, air-tight design in accordance with DIN 18015-5, halogen-free in accordance with DIN VDE 0604-2-100.

Installation opening Ø 70 mm, installation opening Ø 74 mm, depth 48, for panel thickness 12.5-40 mm, with sealing ring Protection class IP 34 according to DIN EN 60529, with 2 screw domes,

8 markings for wire entries up to Ø 10.5 mm using a universal opening cutter (Art. no. 1085-80), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation, for CEE plugs 16 A



Article number:  **9075-78**

EAN: 4013456358812

Inner packing / Packaging quantity: 10 / 100

Price group: 121

Dimensions / Form

Product depth: 50 mm

Drill/cut hole Ø: 74 mm

Assembly / Installation

Min. panel thickness: 12.5 mm

Panel thickness max.: 40 mm

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

air tightness: Yes

Halogen-free: Yes

Approvals / Certifications

VDE: Yes



Certificates



Technical information



Planning data