

Product datasheet:

O-range ECON® conduit one-gang junction box, air-tight, Depth 62 mm

Conduit one-gang junction box O-range ECON®

- Air-tight design with sealing membranes
- fully-insulated through-wiring for combinations of conduit one-gang junction boxes with support connectors
- toolless conduit entries

Pipe-device one-gang junction box, air-tight, for cavity wall installation.
Cavity wall box, designed as a cavity wall pipe-device one-gang junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, air-tight design in accordance with DIN 18015-5, installation opening Ø 60 mm, installation opening Ø 68 mm, depth 62 mm, for panel thickness 7-40 mm, combination distance 71 mm with fully insulated straight couplings, with 2 plus-minus device screws,
Toolless insertion for conduits Ø 20/25 mm (2 x Ø 20 mm, 2 x Ø 25 mm), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Article number:	9266-22
EAN:	4013456548725
Inner packing / Packaging quantity:	25 / 250
Price group:	121

Dimensions / Form

Product depth:	62 mm
Drill/cut hole Ø:	68 mm

Connections / Entries

Number of entries:	4
For conduit Ø:	25 mm

Assembly / Installation

Min. panel thickness:	7 mm
Panel thickness max.:	40 mm
Assembly type:	HW (drywall/lightweight construction)

Safety / Properties

air tightness:	Yes
----------------	-----

Approvals / Certifications

VDE:	Yes
------	-----



Certificates



Planning data

Air-tight conduit one-gang junction box with ECON® technology especially for installation with electrical installation conduit. The box is VDE-certified and suitable for energy-efficient electrical installation acc. to GEG. 4 entries are optimal for continuous conduit installation e. g. in prefabricated house construction or with data networks. Extremely easy fitting thanks to toolless conduit insertion with opening tab. The sealing membrane guarantees permanent air-tightness and at the same time retention of the conduit.

Product datasheet:

- Installation in Ø 68 mm cut hole
- Elastic sealing membrane for guaranteed air-tightness
- Toolless conduit entry
- Can be combined with support connectors, air-tight and fully-insulated