

Product datasheet:

Sound-insulation box 68 Flex

Sound-insulation box 68 Flex

- for sound insulation walls
- for accessories and electronic components
- Air-tight design with sealing membranes
- Elastic tunnel
- can be combined with sound insulation boxes 68

Soundproof one-gang junction box as electronics box for sound insulation walls, Sound insulation box for cavity walls, designed as an electronics box with additional terminal compartment, in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, with sound-absorbing feel and additional external component in the box base area, for sound insulation walls up to 68dB, installation opening Ø 60 mm, installation opening Ø 68 mm, depth 75 mm, combination distance 71 mm, combination with fully insulated straight couplings, for panel thicknesses 7-30 mm, with 2 screw domes and 2 plus-minus device screws, entry markings for 4 electric cables Ø 4-11.5 and 2 conduit entries up to 25 mm, protection class IP30, halogen-free in accordance with DIN VDE 0604-2-100, dimensions: 122x71x75 mm (LxWxH)



Article number: **9068-94**

EAN: 4013456550407

Inner packing / Packaging quantity: 10 / 100

Price group: 192

Dimensions / Form

Product length: 122 mm

Product width: 71 mm

Product depth: 75 mm

Drill/cut hole Ø: 68 mm

Connections / Entries

Number of entries: 6

For conduit Ø: 25 mm

Assembly / Installation

Min. panel thickness: 7 mm

Panel thickness max.: 30 mm

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

Sound insulation walls up to: 68

air tightness: Yes

Halogen-free: Yes

Special application: sound insulation

Sound insulation: Yes



Assembly instructions



Certificates



Planning data

Product datasheet:

Approvals / Certifications

VDE:	Yes
------	-----

Thanks to its solid box body, in connection with the sound absorbing surface on the box base the Sound insulation 68 Flex electronics box guarantees the wall's sound insulation function. Additional insulating strips minimise body sound transfer via the component opening. Fast installation is ideal for modernising or extending existing systems. The flexible tunnel makes it easy to install, and creates space for electronic components, cable reserves and terminals.

- Maintains the wall's sound insulation protection
- For Ø 68 mm installation openings
- Additional sideways terminal compartment for communications and network technology
- Toolless cable and conduit entry
- Can be combined with support connectors, air-tight and fully-insulated