

Product datasheet:

O-range® Acoustic

O-range® Acoustic

- for sound insulation walls
- also for directly opposing installation



Article number:  **5321**

EAN: 5415160009254

Inner packing / Packaging quantity: 10 / 100

Price group: 192

Dimensions / Form

Product depth: 49 mm

Drill/cut hole Ø: 68 mm

Connections / Entries

Number of entries: 6

For conduit Ø: 25 mm

Assembly / Installation

Min. panel thickness: 7 mm

Panel thickness max.: 40 mm

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

Sound insulation walls up to: 69

Halogen-free: Yes

Special application: sound insulation

Sound insulation: Yes



Certificates



Planning data

Thanks to their solid box body in combination with the sound-absorbing surface on the base of the box, O-range® Acoustic one-gang and one-gang junction boxes guarantee the wall's sound insulation. This function is completely maintained even with directly opposing installation. The easy opening process and the 68 mm installation opening ensure fast mounting and also easy retrofitting in existing electrical installations.

- Maintains the wall's sound insulation protection
- Retrofitting is possible
- For Ø 68 mm installation openings
- For a directly opposing installation
- Easy entry for cables up to Ø 11.5 mm and conduits up to Ø 25 mm