

Product datasheet:

One-gang box sound insulation 68

Sound-insulation box 68

- for sound insulation walls
- also for directly opposing installation
- minimum wall thickness 100 mm
- can be combined with each other and with the one-gang junction box

Sound insulation box for sound insulation walls, sound insulation box for cavity walls, designed as a device box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, with sound-absorbing haptics and additional external components in the box base area, for sound insulation walls up to 69dB, installation opening Ø 60 mm, installation opening Ø 68 mm, depth 49 mm, combination distance 71 mm, combination with fully insulated straight couplings, for panel thicknesses 7-40 mm, with 2 screw domes and 2 plus-minus device screws, entry markings for 4 electric cables Ø 4-11.5 and 2 conduit entries up to 25 mm, protection class IP30, halogen-free in accordance with DIN VDE 0604-2-100



Article number: **9069-03**

EAN: 4013456547926

Inner packing / Packaging quantity: 10 / 100

Price group: 192

Dimensions / Form

Product depth: 49 mm

Drill/cut hole Ø: 68 mm

Connections / Entries

Number of entries: 4

For conduit Ø: 25 mm

Assembly / Installation

Min. panel thickness: 40 mm

Panel thickness max.: 40 mm

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

Sound insulation walls up to: 69

Halogen-free: Yes

Special application: sound insulation

Sound insulation: Yes

Approvals / Certifications

VDE: Yes



Certificates



Planning data

Thanks to their solid box body in combination with the sound-absorbing surface on the base of the box, sound insulation 68 one-gang and one-gang junction boxes guarantee the wall's sound insulation. This function is completely maintained even with directly opposing installation. The easy opening process and the 68 mm installation opening ensure fast mounting and also easy retrofitting in existing electrical installations.

Product datasheet:

- Maintains the wall's sound insulation protection
- Also for retrofitting
- For Ø 68 mm installation openings
- For a directly opposing installation
- Easy entry for cables up to Ø 11.5 mm and conduits up to Ø 25 mm