

Product datasheet:

One-gang junction box sound insulation 68

Sound-insulation box 68

- for sound insulation walls
- also for directly opposing installation
- minimum wall thickness 125 mm
- combinable with each other and with the one-gang box

Sound insulation device one-gang junction box for sound insulation walls, sound insulation box for cavity walls, designed as a one-gang junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, with sound-absorbing haptics and additional external component in the box base area, for sound insulation walls up to 69dB, installation opening Ø 60 mm, installation opening Ø 68 mm, depth 61 mm, combination distance 71 mm, combination with fully insulated straight couplings, for panel thicknesses 7-40 mm, with 2 screw domes and 2 plus-minus device screws, entry markings for 6 electric cables Ø 4-11.5 and 2 conduit entries up to 25 mm, protection class IP30, halogen-free in accordance with DIN VDE 0604-2-100



Article number:	9069-04
EAN:	4013456547940
Inner packing / Packaging quantity:	10 / 100
Price group:	192

Dimensions / Form

Product depth:	61 mm
Drill/cut hole Ø:	68 mm

Connections / Entries

Number of entries:	4
For conduit Ø:	25 mm

Assembly / Installation

Min. panel thickness:	40 mm
Panel thickness max.:	40 mm
Assembly type:	HW (drywall/lightweight construction)

Safety / Properties

Sound insulation walls up to:	69
Halogen-free:	Yes
Special application:	sound insulation
Sound insulation:	Yes

Approvals / Certifications

VDE:	Yes
------	-----



Certificates



Planning data

Thanks to their solid box body in combination with the sound-absorbing surface on the base of the box, sound insulation 68 one-gang and one-gang junction boxes guarantee the wall's sound insulation. This function is completely maintained even with directly

Product datasheet:

opposing installation. The easy opening process and the 68 mm installation opening ensure fast mounting and also easy retrofitting in existing electrical installations.

- Maintains the wall's sound insulation protection
- Also for retrofitting
- For Ø 68 mm installation openings
- For a directly opposing installation
- Easy entry for cables up to Ø 11.5 mm and conduits up to Ø 25 mm