

Product datasheet:

Sound-insulation box

Sound-insulation box

- One-gang junction box for sound insulation walls in buildings
- Combination distance of 71 mm through single separation of the pre-embossed edge

Sound insulation box for sound insulation walls, sound insulation box for cavity walls, designed as a one-gang junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, with sound-absorbing sheathing, for sound insulation walls up to 77dB, installation opening Ø 60 mm, installation opening Ø 74 mm, depth 54.5 mm, combination distance 71 mm by cutting off the pre-embossed holding ring, combination with fully insulated straight couplings, for panel thicknesses 7-40 mm, with 2 screw domes and 2 plus-minus device screws, entry markings for 4 NYM cables, cable diameter max. 11.5 mm, protection class IP30, halogen-free in accordance with DIN VDE 0604-2-100



Article number:	9069-01
EAN:	4013456536210
Inner packing / Packaging quantity:	10 / 100
Price group:	192

Dimensions / Form

Product depth:	54.5 mm
Drill/cut hole Ø:	74 mm

Connections / Entries

Number of entries:	4
--------------------	---

Assembly / Installation

Min. panel thickness:	7 mm
Panel thickness max.:	40 mm
Assembly type:	HW (drywall/lightweight construction)

Safety / Properties

Sound insulation walls up to:	77
Halogen-free:	Yes
Special application:	sound insulation
Sound insulation:	Yes

Sound insulation box for use in walls with increased demands on sound protection. The solid box body with additional sound insulation sheathing absorbs and reflects sound, which prevents disturbances in adjacent rooms. Sound insulation is the same as if no installation boxes were installed.

- Maintains the wall's sound insulation protection
- Also for retrofitting
- Installation up to 5-unit combinations
- Also for opposing installation
- Can be used with sound protection cover as a junction box



Assembly instructions



Certificates



Technical information



Planning data