

Product datasheet:

Universal installation housing with mineral fibreboard

Universal installation housings

- with mineral fibreboard for cutting out individual installation holes
- with drilling template (supplied)
- all-round groove indicates the maximum opening size

Universal installation housing, 2-part, for cavity wall installation, cavity wall box, designed as a universal cavity wall installation housing in accordance with DIN EN 60670/VDE 0606, made of plastic with mineral fibreboard.

Base area min. 100 mm x 100 mm, depth min. 50 mm

Opening size max. 70 x 70 mm

Installation depth max. 40 mm

Installation opening 100 x 100 mm, installation opening 4 x Ø 35 mm, depth 53 mm, for panel thickness 7-40 mm, with 4 screw domes and 2 plus-minus device screws, cover with screw fastening,

combined break-out openings for NYM cables and data cables as well as for conduits Ø 20 mm (8 x Ø 20 mm, 8 x 3 x 1.5 mm², 4 x low voltage), for 2 electrical circuits, for terminals up to 4 mm², protection class IP 30 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Planning data

Article number: **9195-22**

EAN: 4013456532229

Packaging quantity: 10

Price group: 120

Dimensions / Form

Product length: 105 mm

Product width: 105 mm

Product depth: 53 mm

Installation opening (wall/ceiling) Ø: 4x35 mm

Drill/cut hole Ø: 4x35 mm

Connections / Entries

For conduit Ø: 20 mm

Assembly / Installation

Assembly type: HW (drywall/lightweight construction)

Universal installation housings for a wide range of device installations always ensure optimum space for all kinds of devices. The intelligent housing design ensures stability and a secure fit in the wall.

- For displays, LED lights and much more
- For installing almost all shapes and sizes
- Mineral fibreboard allows individual installation opening
- With FX⁴ quick assembly technology