

Product datasheet:

Junction box Ø 120 mm

Junction casings and boxes

- receptacle for TS 35 standard rail
- Make cut hole with Variocut 1089-00 in fully extended position or bi-metallic cutter 1082-20
- including cover

Junction box, for cavity wall installation.

Cavity wall box, designed as a cavity wall junction box in accordance with DIN EN 60670/VDE 0606, made of plastic, installation opening Ø 120 mm, depth 65 mm, for panel thickness 7-40 mm, with slot for TS 35 standard rail, with cover, with 2 screw domes and 2 plus-minus device screws, Toolless entry for NYM cables and data cables as well as for conduits Ø 20/25 mm (4 x Ø 25 mm, 2 x Ø 20 mm, 4 x 3 x 1.5 mm², 4 x 3 x 2.5 mm² or 5 x 1.5 mm², 2 x 5 x 2.5 mm² or 7 x 1.5 mm², 6 x low voltage), protection class IP 30 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Article number: **9073-01**

EAN: 4013456221017

Packaging quantity: 10

Price group: 120

Dimensions / Form

Product depth: 65 mm

Drill/cut hole Ø: 120 mm

Connections / Entries

For conduit Ø: 20 mm

Assembly / Installation

Assembly type: HW (drywall/lightweight construction)

Approvals / Certifications

VDE: Yes



Certificates



Planning data

Junction casings in all sizes and for almost any kind of installations. This product range features practical housing sizes as well as a robust housing design which is perfect for building sites.

- As central junction casings for star-shaped cable laying
- Easy to rewire when changing the way rooms are used
- With separator walls for safe separation of electrical circuits
- Create precise wall openings using the drilling template supplied
- End cover with screw fastening for VDE-compliant installation