

Product datasheet:

Junction casing 240 x 140 x 72 mm

Junction casings and boxes

- for installation DIN terminal strips, TS 35 standard rails for terminal strips, etc., terminal blocks up to 16 mm²
- with drilling template (supplied)
- including cover

Junction box, for cavity wall installation, cavity wall box, designed as a cavity wall junction casing in accordance with DIN EN 60670/VDE 0606, made of plastic. Installation opening 200 x 100 mm, installation opening 4 x Ø 68 mm, depth 72 mm, for panel thickness 7-40 mm, with 4 screw domes and 2 plus-minus device screws, cover with screw fastening, combination break-out openings for NYM cables and data cables as well as for conduits Ø 20/25/32 mm (8 x Ø 20 mm, 2 x Ø 25 mm, 2 x Ø 32 mm, 20 x 3 x 1.5 mm², 6 x data cable), for max. 3 electrical circuits, for terminals up to 16 mm², protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Article number:	9192-91
EAN:	4013456230002
Packaging quantity:	10
Price group:	120

Dimensions / Form

Product length:	240 mm
Product width:	140 mm
Product depth:	72 mm
Drill/cut hole Ø:	4x68 mm

Connections / Entries

For conduit Ø:	20 mm
----------------	-------

Assembly / Installation

Assembly type:	HW (drywall/lightweight construction)
----------------	---------------------------------------

Approvals / Certifications

VDE:	Yes
------	-----



Certificates



Planning data

Junction casings in all sizes and for almost any kind of installations. This product range features practical housing sizes as well as a robust housing design which is perfect for building sites.

- As central junction casings for star-shaped cable laying
- Easy to rewire when changing the way rooms are used
- With separator walls for safe separation of electrical circuits
- Create precise wall openings using the drilling template supplied
- End cover with screw fastening for VDE-compliant installation