

Product datasheet:

Potential equalisation casing 10²

Junction casings and boxes

- for bathrooms or similar
- with potential equalisation rail, protected against corrosion
- with 4 screw domes
- With Ø 3.2 x 15 mm cover screws
- including cover

Junction box, for cavity wall installation, cavity wall box, designed as a cavity wall junction casing in accordance with DIN EN 60670/VDE 0606, made of plastic. Installation opening 100 x 100 mm, installation opening 4 x Ø 35 mm, depth 53 mm, for panel thickness 7-40 mm, with 4 screw domes and 2 plus-minus device screws, cover with screw fastening, combined break-out openings for NYM cables and data cables as well as for conduits Ø 20 mm (8 x Ø 20 mm, 8 x 3 x 1.5 mm², 4 x low voltage), equipotential bonding bar for 6 electric cables up to 10 mm², one electric cable up to 16 mm², protection class IP 30 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Planning data

Article number: **9195-73**

EAN: 4013456230309

Inner packing / Packaging quantity: 1 / 10

Price group: 120

Dimensions / Form

Product length: 105 mm

Product width: 105 mm

Product depth: 53 mm

Drill/cut hole Ø: 4x35 mm

Assembly / Installation

Assembly type: HW (drywall/lightweight construction)

Junction casings in all sizes and for almost any kind of installations. This product range features practical housing sizes as well as a robust housing design which is perfect for building sites.

- As central junction casings for star-shaped cable laying
- Easy to rewire when changing the way rooms are used
- With separator walls for safe separation of electrical circuits
- Create precise wall openings using the drilling template supplied
- End cover with screw fastening for VDE-compliant installation