

Product datasheet:

Large slab ceiling box 115

Ceiling junction box

- Installation height 115 mm, with M5 metal nut for light hook (min. hook length: 115 mm + plaster thickness)
- with screw-on cover for on-site fitting of conduits
- Suitable for all types of form-work
- Maximum light hook load according to DIN EN 60670 100 N (10 kg)

Concrete construction, ceiling junction box, 3-piece, exit opening Ø 60 mm, depth 115 mm, with M5 metal nut for light hook mounting

Ceiling junction box for concrete construction installation, on-site mixed concrete, fixing to formwork

Concrete construction box, designed as a large ceiling luminaire box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic

Installation opening Ø 60 mm, diameter Ø 102 mm, depth 115 mm, closing cover with M5 metal nut for slot for mounting light hooks in accordance with DIN EN 60670 (100N), front part can be swung out, with 2 screw domes

Entry markings for electrical installation conduits (8 x up to 25 mm) and (4 x up to 32 mm) and for cables and electric cables (12 x up to Ø 16 mm), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for concrete construction installation precast concrete



Certificates



Planning data

Article number:	1227-50
EAN:	4013456330504
Packaging quantity:	100
Price group:	130

Dimensions / Form

Product Ø:	102 mm
Product depth:	115 mm

Connections / Entries

Number of entries:	12
For conduit Ø:	32 mm

Assembly / Installation

Assembly type:	BB (solid construction)
----------------	-------------------------

Safety / Properties

Special application:	on-site mixed concrete
----------------------	------------------------

Approvals / Certifications

VDE:	Yes
------	-----

Ceiling junction box to accommodate electrical connections. With the optional light hook, the box is also ideally suited for installing and attaching luminaires. The wide range of ceiling boxes permits almost all conceivable installations.

- Suitable for all types of formwork
- Flat front part for fast, easy nailing
- Integrated cap nut ensures secure fitting of an M5 light hook acc. to DIN EN 60670

Product datasheet:

- The colour system ensures that the installation can be checked quickly