

Product datasheet:

One-gang box CEE

One-gang and one-gang junction boxes

- device screws distance 67 mm
- With sealing ring for protection class IP 34 and 2 raised head 4 mm Ø device screws, length 20 mm
- for use with 16A CEE equipment inserts
- Suitable for all types of form-work

concrete construction, device box for CEE device inserts 16 A, 3-piece, installation opening Ø 70 mm, depth 66 mm

Device box for concrete construction installation, on-site mixed concrete, fixing to formwork.

Concrete construction box, designed as a concrete construction device box for CEE device inserts 16 A, made of plastic

Installation opening Ø 70 mm, length 80 mm, width 80 mm, depth 66 mm, with sealing ring for protection class IP34, front part can be swung out, with 2 screw domes spaced 67 mm apart, with 2 raised head device screws Ø 4 x 20 mm, with integrated support element attachment Ø 20 mm for installation on opposing formwork

Entry markings for electrical installation conduits (2 x up to 25 mm) and for cables and electric cables (2 x up to Ø 16 mm), protection class IP 34 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100, for concrete construction installation using on-site mixed concrete



Technical information



Planning data

Article number:  **1275-40**

EAN: 4013456310407

Inner packing / Packaging quantity: 10 / 100

Price group: 130

Dimensions / Form

Product depth: 66 mm

Cover for box/housing/casing Ø: 70 mm

Connections / Entries

Number of entries: 2

For conduit Ø: 25 mm

Assembly / Installation

Assembly type: BB (solid construction)

Safety / Properties

Special application: on-site mixed concrete

One-gang box and one-gang junction box for installation in vertical formwork. A modular programme with 2-piece or 3-piece boxes, which are easily nailed to the formwork with the flat front parts. The extra-flexible design ensures integrated spring travel and provides secure support between the formwork.

- Suitable for all types of formwork
- High torsional strength, can be combined with a standard distance of 71 mm
- Combinations have fully-insulated cable transitions
- Support in base of box does not block any conduit entry
- Integrated spring travel ensures secure support

Product datasheet:

· dimensions in accordance with German DIN 49073