

Product datasheet:

Junction box

One-gang and one-gang junction boxes

- cover screw distance 67 mm
- Suitable for all types of form-work

Concrete construction, junction box, 2-piece, installation opening Ø 70 mm, depth 66 mm

Junction box for concrete construction installation, on-site mixed concrete, fixing to formwork

Concrete construction box, designed as a concrete construction junction box, made of plastic

Installation opening Ø 70 mm, length 80 mm, width 80 mm, depth 66 mm, front part can be swung out, with 2 screw domes spaced 67 mm apart, with integrated support element attachment Ø 20 mm for installation on opposing formwork

Insertion markings for electrical installation conduits (2 x up to 25 mm) and for cables and electric cables (2 x up to Ø 16 mm), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100, for concrete construction installation using on-site mixed concrete



Planning data

Article number:  **1276-71**

EAN: 4013456331112

Inner packing / Packaging quantity: 10 / 100

Price group: 130

Dimensions / Form

Product depth: 66 mm

Cover for box/housing/casing Ø: 70 mm

Connections / Entries

For conduit Ø: 25 mm

Assembly / Installation

Assembly type: BB (solid construction)

Safety / Properties

Special application: on-site mixed concrete

One-gang box and one-gang junction box for installation in vertical formwork. A modular programme with 2-piece or 3-piece boxes, which are easily nailed to the formwork with the flat front parts. The extra-flexible design ensures integrated spring travel and provides secure support between the formwork.

- Suitable for all types of formwork
- High torsional strength, can be combined with a standard distance of 71 mm
- Combinations have fully-insulated cable transitions
- Support in base of box does not block any conduit entry
- Integrated spring travel ensures secure support
- dimensions in accordance with German DIN 49073