

Product datasheet:

Ceiling strip (ceiling exit) Ø 20 mm

Ceiling strips

- Ceiling exit for intermediate wall feed, exit or conduit connector
- Accepts large tolerance compensation
- Open on formwork side
- Use wire-pull casing and junction casing 9914.01 for DIN EN conduits up to Ø 63 mm

Concrete construction, ceiling strip (ceiling exit), for 20 mm conduits, 1-piece, 138 x 36 x 29 mm

Ceiling strip for concrete construction installation, on-site mixed concrete, fixing to formwork

Ceiling strip for installation conduit exit 20 mm, made of plastic, open to the formwork side, for feeding into partition walls or as ceiling exit

Length 135 mm, width 36 mm, depth 29 mm, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for concrete construction installation, on-site mixed concrete



Article number:	 1283-33
EAN:	4013456357624
Inner packing / Packaging quantity:	25 / 100
Price group:	130



Technical information



Planning data

Dimensions / Form

Product length:	138 mm
Product width:	36 mm
Product depth:	29 mm

Connections / Entries

Number of entries:	2
For conduit Ø:	20 mm

Assembly / Installation

Assembly type:	BB (solid construction)
----------------	-------------------------

Safety / Properties

Special application:	on-site mixed concrete
----------------------	------------------------

Ceiling strips for intermediate wall feeds, as ceiling exit or for connecting installation conduits. The elongated shape allows for compensation of big tolerances for lightweight intermediate wall feeds.

- For DIN EN conduits Ø 20 to Ø 25 mm
- Large tolerance compensation
- Exiting of two conduits at one exit site
- Can be combined for more than one adjacent exit
- Space for conduit ends for extending with conduit bushes