

Product datasheet:

Conduit transition coupling Ø 32 mm

B² conduit connectors

- For toolless connection of Ø 32 mm conduits to the B² one-gang junction boxes 1262-XX and 1263-XX
- Accepts rigid and flexible conduits
- Damping of conduit vibrations during the compaction process
- Prevents the conduits from penetrating the B² one-gang junction boxes and thus avoids subsequent conduit shortening



Concrete construction, conduit transition coupling Ø 32 mm, for 32 mm conduits, 1-piece

Conduit transition coupling Ø 32 mm for concrete construction installation, precast concrete

Pipe transition coupling Ø 32 mm, for toolless pipe conduit connection to the B2 one-gang junction boxes 1262-xx and 1263-xx, for rigid and flexible installation conduits 32 mm, flame retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100, for precast concrete construction installation

Article number: **1263-32**

EAN: 4013456586864

Packaging quantity: 100

Price group: 140

Connections / Entries

For conduit Ø: 32 mm

Assembly / Installation

Assembly type: BB (solid construction)

Safety / Properties

Special application: precast concrete

The range of B² conduit connectors offers a secure and toolless conduit connection to the B² one-gang junction boxes without the need for special tools. The conduit connection created using a conduit connector is absolutely impermeable to concrete and safely dampens the vibrations of the conduits during the compaction process. As the conduit connection is made outside the B² one-gang junction boxes, no conduit protrudes into the interior of the box, thus eliminating the need to shorten the conduit on the inside. With the new 90° conduit connectors, sideways conduit connections can now also be easily implemented in narrow installation areas.

- Toolless conduit connection, no special tools required
- Precisely fitting "variable" conduit connection, absolutely sealed against concrete
- Damping of vibrations during the high-frequency or low-frequency compression process
- Conduit connection outside the one-gang junction box, no conduits protruding into the interior of the box
- Conduit connectors 90° for the lateral connection of conduits in narrow installation areas