

Product datasheet:

60° conduit connector

B² conduit connectors

- space-saving entry of conduits in confined spaces, e.g. door and window areas
- for punching out markings without tools
- for fitting flexible 25 mm DIN EN conduits



Article number:  **1266-25**

EAN: 4013456547711

Packaging quantity: 100

Price group: 140

Assembly / Installation

Assembly type: BB (solid construction)

Safety / Properties

Special application: precast concrete



Planning data

The range of B² conduit connectors offers a secure and toolless conduit connection to the B² one-gang junction boxes without the need for special tools. The conduit connection created using a conduit connector is absolutely impermeable to concrete and safely dampens the vibrations of the conduits during the compaction process. As the conduit connection is made outside the B² one-gang junction boxes, no conduit protrudes into the interior of the box, thus eliminating the need to shorten the conduit on the inside. With the new 90° conduit connectors, sideways conduit connections can now also be easily implemented in narrow installation areas.

- Toolless conduit connection, no special tools required
- Precisely fitting "variable" conduit connection, absolutely sealed against concrete
- Damping of vibrations during the high-frequency or low-frequency compression process
- Conduit connection outside the one-gang junction box, no conduits protruding into the interior of the box
- Conduit connectors 90° for the lateral connection of conduits in narrow installation areas