

## Product datasheet:

# B<sup>2</sup> one-gang junction box with plaster skin, depth 48.5 mm

## B<sup>2</sup> one-gang junction boxes

- for in-factory installation
- Fastening to the formwork by means of KAISER adhesive foil (Art. No. 1219-00) or hot glue
- 4 screw domes and 2 expanding claw fields for accessory fitting
- Standardised combination distance 71 mm
- 1-piece

Concrete construction B<sup>2</sup> one-gang junction box, with plaster skin, 1-piece, depth 48.5 mm

One-gang junction box for concrete construction installation, precast concrete, adhesive attachment on steel formwork

Concrete construction box, designed as a concrete construction one-gang junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, with plaster skin

Installation opening Ø 60 mm, length 77 mm, width 76 mm, depth 48.5 mm, conduit entry by punching with conduit connector, with integrated conduit retention, front part can be swung out, can be connected in a row with torsion-proof connection in a combination distance of 71 mm without device screws, fully insulated cable transition, with 4 screw domes and 2 expanding claw fields, without device screws

Insertion markings for electrical installation conduits (4 x 20/25 mm), Insertion markings for electrical installation conduits (4 x 16 mm) and insertion markings for cables and electric cables (8 markings up to Ø 16 mm), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100, for concrete construction installation precast concrete



Certificates



Technical information



Planning data

**Article number:**  **1262-60**

**EAN:** 4013456142893

**Packaging quantity:** 100

**Price group:** 140

### Dimensions / Form

**Product depth:** 48.5 mm

**Cover for box/housing/casing Ø:** 60 mm

### Connections / Entries

**Number of entries:** 4

**For conduit Ø:** 25 mm

### Assembly / Installation

**Assembly type:** BB (solid construction)

### Safety / Properties

**Special application:** precast concrete

### Approvals / Certifications

**VDE:** Yes

## Product datasheet:

B<sup>2</sup> system for installation in horizontal precast concrete. All installation requirements can be met with just a few components. The one-gang boxes are self-adhesive and the accessories provide a practical product range.

- Extremely time-saving
- One-piece design
- Available with or without plaster skin
- Available prefabricated with special glue – no adhesive residues when removing formwork
- Simple connectors for combinations or opposing boxes