

Product datasheet:

Oval funnel for M25 conduits

Oval funnel

- for the simple connection of DIN EN conduits with tolerance compensation for wall-wall and wall-ceiling transitions
- for installation on the transition edge
- accepts rigid and flexible DIN EN conduits
- with closing cover to prevent ingress of material

Concrete construction, oval funnel, for 25 mm conduits, with closing cover, 1-piece
Oval funnel for concrete construction installation, precast concrete, adhesive attachment to steel formwork

Oval funnel for connecting rigid and flexible installation conduits 25 mm, made of plastic, can be closed on the formwork side with a closing cover, with tolerance compensation of 2 cm in the longitudinal direction and 1 cm in the transverse direction, for continuous empty piping at transitions of precast concrete elements,

For installation on side formwork, flame-retardant in accordance with DIN EN 60695 up to 650°C, halogen-free in accordance with DIN VDE 0604-2-100, for precast concrete construction installation



Planning data

Article number:  **1261-43**

EAN: 4013456533462

Packaging quantity: 100

Price group: 140

Connections / Entries

For conduit Ø: 25 mm

Assembly / Installation

Assembly type: BB (solid construction)

Safety / Properties

Special application: precast concrete

The oval funnel simplifies the exact joining of prefabricated concrete elements with integrated installation conduits. It guarantees safe conduit entry and provides a tolerance compensation of 1 cm or 2 cm during installation.

- Tolerance compensation when joining the concrete elements
- For industrially prefabricated ceiling and wall elements as well as on-site mixed concrete
- For secure connection of installation conduits on transitions of prefabricated concrete elements
- Precise joining of electrical installation conduits
- Tolerance compensation: 2 cm in longitudinal direction and 1 cm in transverse direction.