

Product datasheet:

Large slab ceiling box 115

Large slab ceiling box

- for in-factory installation
- Fastening to the formwork by means of KAISER adhesive foil (Art. No. 1219-00) or hot glue
- Installation height 115 mm, with M5 metal nut for light hook (min. hook length: 115 mm + plaster thickness)
- With closing cover for on-site fitting of conduits
- Maximum light hook load according to DIN EN 60670 100 N (10 kg)

Concrete construction, ceiling junction box, 2-piece, exit opening Ø 60 mm, depth 115 mm, with M5 metal nut for light hook slot

Ceiling junction box for concrete construction installation, precast concrete, adhesive attachment on steel formwork

Concrete construction box, designed as a large slab ceiling box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic

Installation opening Ø 60 mm, diameter Ø 102 mm, depth 115 mm, closing cover with M5 metal nut for mounting light hooks in accordance with DIN EN 60670 (100N), front part can be swung out, with 2 screw domes

Entry markings for electrical installation conduits (8 x up to 25 mm) and (4 x up to 32 mm) and for cables and electric cables (12 x up to Ø 16 mm), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for concrete construction installation precast concrete



Certificates



Planning data

Article number:  1227-55

EAN: 4013456330511

Packaging quantity: 100

Price group: 110

Dimensions / Form

Product depth: 115 mm

Connections / Entries

Number of entries: 12

For conduit Ø: 32 mm

Assembly / Installation

Assembly type: BB (solid construction)

Safety / Properties

Special application: precast concrete

Approvals / Certifications

VDE: Yes

Large slab ceiling box for factory installation in prefabricated ceilings. The large slab ceiling boxes are already integrated in the ceilings when these arrive at the building site. This permits fast on-site laying of empty conduits.

- Large adhesive area with rough surface structure for a secure fit on the formwork table
- Installation height guarantees optimal transport conditions for prefabricated ceilings

Product datasheet:

- Quick-release cover for fast cutting of conduit entries using punch pliers
- Integrated M5 domed cap nut ensures secure fitting of a light hook.