

Product datasheet:

Prefix® universal support

Prefix® universal support

- For electrical installations on the opposing formwork side.
- Facilitates fixing to the reinforcement
- Adjustable to concrete ceilings 20, 25, 30 or 35
- Pre-fixing by means of Prefix® installation technology
- Can be used for the following articles:
- End and transition bushes / item no. 1261-82/-83/-84
- Wall and ceiling transitions 30° / item no. 1261-92/-93/-94
- Wall and ceiling transitions 90° / item no. 1261-95/-96/-97



Article number:  **1261-00**

EAN: 4013456552357

Packaging quantity: 350

Price group: 140

Dimensions / Form

Product length: 87 mm

Product width: 45 mm

Product depth: 36 mm

Assembly / Installation

Minimum concrete cover: 20.25.30.35 mm

Max. concrete cover: 20.25.30.35 mm

Assembly type: BB (solid construction)

Safety / Properties

Special application: precast concrete



Assembly instructions



Planning data

The Prefix® universal support enables simple, fast fitting of electrical installations in solid wall elements on the opposing formwork side without a support element for the steel formwork table. The support can be easily adjusted to the required concrete ceiling by means of a snap-in connection and attached to the new end and transition bushes, wall and ceiling transitions 30° and wall and ceiling transitions 90° by means of a snap-in connection. The previously customary and costly in-house constructions using timber blanks can thus be dispensed with, disruptions to the further production process are a thing of the past and production of a good wall surface quality is guaranteed without restriction.

- For overhead electrical installations in prefabricated solid walls without support elements
- With integrated dimension indication, easily adjustable to the common concrete ceilings 20 mm, 25 mm, 30 mm or 35 mm
- Generous tolerance compensation for fixing to the reinforcement
- Prefixing using Prefix® installation technology leaves both hands free for fixing with tie wires