

Product datasheet:

Wall and ceiling transition 90° Ø 20 mm

Wall and ceiling transitions

- For connecting conduits at transition points
- Slot for system magnet (Art.-No. 1299-69) and system magnet PLUS (Art.-No. 1299-70)
- Large adhesive surface
- Ideally suited for the construction of a rigid conduit system
- For overhead installation in solid walls
- With closing cover to prevent ingress of foreign bodies
- Can be combined with end and transition grommets and 30° wall and ceiling bends
- Two slots for Prefix® system accessories
- Suitable for all types of formwork
- Two nail domes



Concrete construction, wall-ceiling transition 90°, for 20 mm conduits, with closing cover, 2-piece pre-assembled, 105 x 64 x 78 mm

Wall-ceiling transition for precast concrete construction installation, precast concrete, fixing to steel formwork using system magnet (1299-69 or 1299-70)

Wall-ceiling transition for connecting 20 mm installation conduits or as a wall or ceiling exit, made of plastic, can be closed on the formwork side with a closing cover, for continuous empty piping at transitions of precast concrete elements

For magnet attachment with system magnet (1299-69 or 1299-70), for adhesive attachment, for nailing, for overhead installations in solid wall elements without support element Fixing to reinforcement with Prefix® universal support seat (1261-00), with signal bristle

Length 105 mm, width 64 mm, depth 78 mm, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for precast concrete construction installation



Technical information



Planning data

Article number:  **1261-95**

EAN: 4013456588356

Packaging quantity: 100

Price group: 140

Dimensions / Form

Product length: 105 mm

Product width: 64 mm

Product depth: 78 mm

Connections / Entries

Number of entries: 1

For conduit Ø: 20 mm

Assembly / Installation

Assembly type: BB (solid construction)

Safety / Properties

Special application: precast concrete

For the first time, the new end and transition grommets, wall and ceiling bends , 30°, and wall and ceiling transitions 90° allow the automated positioning and fastening of conduit connections in precast concrete elements. The integrated slot for the system magnets (Art. No. 1299-69) and system magnet PLUS (Art. No. 1299-70) enables a safe,

Product datasheet:

formwork-flush fit on the horizontal steel formwork for the circulation systems used in the concrete plants. The new items also provide alternative options for fixing to formwork. They can be fixed using hot glue, steel nails and even for overhead installation in solid wall elements using Prefix® Universal supports (Art. No. 1261-00).

- Slot for system magnet (Art. No. 1299-69) and system magnet PLUS (Art. No. 1299-70) for use in automated production lines
- For conduit sizes of Ø 20 mm, Ø 25 mm and Ø 32 mm
- All end and transition grommets, wall and ceiling elbows 30° and wall and ceiling transitions 90° can be combined with each other
- Resealable sealing cover to protect the empty conduit system from concrete when installed on top, during transport and when erected on site
- Signal bristle and bold colouring for easy retrieval in the concrete surface
- Optimal elbow radius for easy cable insertion
- 1-part design, immediately ready for use