

Product datasheet:

HaloX® 100 installation kit

HaloX® 100 installation kit

- for retrofitting of HaloX®-O housings into slab ceilings
- required hole size Ø 150-160 mm

HaloX® 100 installation kit, for retrofitting in slab ceilings
 Front part for concrete construction installation, on-site mixed concrete, for retrofitting HaloX® 100 installation housings in slab ceilings
 Plastic installation kit, depth 30 mm, for insertion between housing and front part, suitable for housing (1281-XX and 1290-30), with lateral support seats for dowel fixing, flame retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100



Article number:  **1281-20**

EAN: 4013456546783

Packaging quantity: 10

Price group: 150

Dimensions / Form

Product depth: 30 mm

Assembly / Installation

Assembly type: BB (solid construction)

Safety / Properties

Special application: on-site mixed concrete



Planning data

HaloX® 100 installation kit can be retrofitted in existing slab ceilings (50 mm thickness and greater) with or without transformer tunnel.

- For retrofitting in slab ceilings
- Minimal effect on statics
- Large selection of opening sizes up to Ø 100 mm
- Extension rings for bridging the slab ceiling element and for increasing the luminaire installation depth