

Product datasheet:

Signal cover Ø 68 mm for HaloX®

Signal cover

- Protects the interior of the housing
- Three stable signal bristles and strong colouring for easy retrieval from the plastered rough ceiling.
- Serrated edge structure for a clean installation opening



Article number:	1281-31
EAN:	4013456580954
Inner packing / Packaging quantity:	10 / 100

Dimensions / Form

Cover for box/housing/casing Ø:	68 mm
---------------------------------	-------

Assembly / Installation

Assembly type:	BB (solid construction)
----------------	-------------------------

Safety / Properties

Special application:	on-site mixed concrete
----------------------	------------------------

Features

Cover design:	Construction protection cover/plaster cover
cover fastening:	Latch on



Planning data

ETIM Product classification:

Cover for box/housing for built-in mounting in the wall/ceiling

Diameter:	68 mm
Suitable for box-/housing diameter:	
Length:	
Suitable for box-/housing length:	
Width:	
Suitable for box-/housing width:	
Depth:	
Shape:	Round
Type of fastening:	Plug-in cover
Model:	Signalling cover
With cable outlet:	No
Material:	Plastic
Halogen free:	No
Colour:	Red
RAL-number (similar):	

Product datasheet:

With screws:	No
Sealable:	No

The new signal cover ensures a clean ceiling appearance and avoids time-consuming reworking of the installation opening after plastering. As an accessory item for the KAISER HaloX® concrete installation housings, the signal cover is simply inserted into the already opened front part after formwork removal from the rough ceiling or wall. Thus, the installation opening is securely closed and protected against penetration of plaster. Three signal bristles, in combination with the bright red colour, ensure that the installation opening in the plastered rough ceiling or wall can be found quickly and easily. The installation opening can be opened with one targeted blow of the hammer without destroying the surrounding plaster pattern. With one turn of the knife edge, cleaning residues are removed effortlessly. The flexible signal cover can then be removed easily and cleanly. Its specially serrated edge structure preserves the plaster edge.

- Stable and robust clamping in installation diameters of Ø 68 mm, Ø 75 mm and Ø 80 mm
- For use in fixed HaloX® front parts, universal HaloX® front parts and other installation openings
- Stable signal bristles and strong colouring for easy retrieval from the plaster surface
- Reusable, easy to clean