

Productgegevensblad:

Stucdeksel Ø 80 mm for HaloX®

Signal cover

- Protects the interior of the housing
- Three stable signal bristles and strong colouring for easy retrieval from the plastered rough ceiling.
- Serrated edge structure for a clean installation opening



Artikelnummer: 1281-33

EAN: 4013456581005

Verpakking binnenkant / 10 / 100
Verpakkingshoeveelheid:

Afmetingen / Vorm

Deksel voor doos/behuizing/kast Ø: 80 mm

Montage / Installatie

Montagetype: BB (massieve constructie)

Veiligheid / Eigenschappen

Speciale toepassing: Stortbeton

Uitrusting

Uitvoering deksel: Bouwbeschermingsdeksel/pleisterdeksel

Dekselbevestiging: Vergrendelbaar



Planningsgegevens

ETIM Productklasse:

Deksel voor doos/behuizing voor montage in wand/plafond

Diameter: 80 mm

Voor doosdiameter:

Lengte:

Voor dooslengte:

Breedte:

Voor doosbreedte:

Diepte:

Vorm: Rond

Soort bevestiging: Opklikdeksel

Uitvoering: Signalisatiedeksel

Met kabeluitgang: Nee

Materiaal: Kunststof

Halogeenvrij: Nee

Kleur: Rood

RAL-Nummer (vergelijkbaar):

Productgegevensblad:

Met schroeven:	Nee
Verzegelbaar:	Nee

The new signal cover ensures a clean ceiling appearance and avoids time-consuming reworking of the installation opening after plastering. As an accessory item for the KAISER HaloX® concrete installation housings, the signal cover is simply inserted into the already opened front part after formwork removal from the rough ceiling or wall. Thus, the installation opening is securely closed and protected against penetration of plaster. Three signal bristles, in combination with the bright red colour, ensure that the installation opening in the plastered rough ceiling or wall can be found quickly and easily. The installation opening can be opened with one targeted blow of the hammer without destroying the surrounding plaster pattern. With one turn of the knife edge, cleaning residues are removed effortlessly. The flexible signal cover can then be removed easily and cleanly. Its specially serrated edge structure preserves the plaster edge.

- Stable and robust clamping in installation diameters of Ø 68 mm, Ø 75 mm and Ø 80 mm
- For use in fixed HaloX® front parts, universal HaloX® front parts and other installation openings
- Stable signal bristles and strong colouring for easy retrieval from the plaster surface
- Reusable, easy to clean