

Product datasheet:

HaloX® 250 with tunnel for precast concrete for magnet attachment

HaloX® concrete installation housing (precast concrete)

- One-part housing for holding the system magnet (Art. No. 1299-69) and system magnet PLUS (Art. No. 1299-70)
- Tool-free combination feed for M20/M25 pipes.
- Conduit entry limitation to prevent the need to shorten the conduit inside.
- Suitable with signal cover

Installation housing, HaloX® 250 with tunnel 325, with magnetic recess, for slab ceilings
Installation housing for concrete construction installation, precast concrete, fixing to steel formwork using system magnet (1299-69 or 1299-70)

Concrete installation housing made of plastic, for individually customisable installation openings up to Ø 250 mm and for compensating for installation tolerances, with tunnel 325 for operating units up to max. 280 mm x 90 mm x 50 mm, housing Ø 280 mm, housing depth 120 mm, tunnel dimensions: length 325 mm, width 140 mm, height 85 mm, lamp power LED max. 45 W, lamp power NV/HV/TC max. 100 W

Toolless combination entries for 4 x 20 mm/25 mm conduits with integrated conduit retention and conduit entry limit to prevent internal conduit shortening, force-locking catch mechanism, can be re-aligned retrospectively, conduit entries can be resealed, flame-retardant in accordance with DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100



Planning data

Article number: **1283-76**

EAN: 4013456548473

Packaging quantity: 10

Dimensions / Form

Product Ø: 280 mm

Product depth: 120 mm

Connections / Entries

For conduit Ø: 25 mm

Assembly / Installation

Room boundary type: wall

Assembly type: BB (solid construction)

Room delimitation type Design: Concrete

Safety / Properties

Power consumption in housing LED: 45 W

Special application: precast concrete

Features

Design: 1-fold

Expandability/Combinability: No

Product datasheet:

Integrated accessories: with tunnel

Fitting

Fastening type Industrial production: Magnet attachment (manual setting)

ETIM Product classification:

Accessories/spare parts for luminaire mounting box

Type of accessory/spare part: Universal front piece

Accessory: No

Spare part:

System HaloX® is designed as a single piece for fitting in precast concrete. The housings can easily be aligned on the formwork table by means of markings on the housing. The housing with pre-fitted mineral fibreboard allows easy glueing and the housings can be turned by 360° on the formwork table even after glueing. Housings with pre-fitted front parts to hold the system magnet (Art. No. 1299-69/1299-70) are available for magnet attachment. Laying tolerances which may occur during the fitting of panel elements are compensated for via the housing sizes in connection with a variable cut-out area.

Because of the compact dimensions of the housings, the reinforcement can easily be placed around the housing. For luminaires or loudspeakers with installation depths equal to or greater than 110 mm, the installation compartment of the HaloX® housings can be increased on the on-site concrete building site by means of extension rings. The fitting of the conduits on-site takes place without the need for tools for M20/M25 conduits without any internal shortening of the conduits.

- For precast concrete slab ceilings and wall elements.
- 3 housing sizes with and without tunnel
- Single-part housings with integrated mineral fibreboard for easy adhesive fixing
- One-part housings with plastic panel for magnet attachment
- Toolless entry technology for 20/25 mm conduits
- Compensation for laying tolerances on the concrete building site
- Optimal heat management thanks to maximum surface contact with the concrete