

Product datasheet:

HaloX® housing for drilling holes in solid ceilings

For retrofitting

- For retrofitting in solid concrete ceilings.
- Core drilling Ø 150 - 160 mm.
- Take into consideration the ceiling thickness - at least 3 cm concrete cover is needed on top of the box.
- Suitable for front panels or spacer rings with an item number beginning with 1281-XX.



Article number:	1290-30
EAN:	4013456336667
Packaging quantity:	10

Dimensions / Form

Product Ø:	130 mm
Product depth:	133 mm

Assembly / Installation

Assembly type:	BB (solid construction)
----------------	-------------------------

Safety / Properties

Power consumption in housing LED:	20 W
Special application:	on-site mixed concrete



Planning data

ETIM Product classification: Built-in installation box luminaire

Suitable for high voltage luminaires:	No
Suitable for low voltage luminaires:	No
Suitable for LED luminaires:	No
Suitable for lamp power:	
Application:	For cast-in-place concrete
With space for gear:	
Built-in diameter:	
Built-in length:	
Built-in width:	
Built-in height/depth:	133 mm
Max. luminaire diameter:	130 mm
Min. ceiling thickness:	
Material:	Plastic

HaloX® concrete installation housing for solid concrete ceilings can be inserted into existing and retrofitted drilling holes.

Product datasheet:

- For retrofitting in solid ceilings
- Minimal effect on statics
- Quick installation with snap-in connections
- Robust construction, ideal for use on building sites
- Large selection of opening sizes up to Ø 100 mm