

Product datasheet:

KompaX®1 housing for on-site mixed concrete

KompaX® 1 concrete installation housing

- installation height for built-in luminaires or loudspeakers max. 100 mm
- consists of front and rear parts
- only in combination with front rings 1293-16 up to 1293-71, in facing concrete with front rings 1293-80 to 1293-87
- incl. support elements for installation heights 100/150/200 mm

Installation housing, KompaX® 1

Installation housing for concrete construction installation, on-site mixed concrete, fixing to formwork

Plastic concrete installation housing, for luminaires and loudspeakers Ø 160 to 300 mm, length 585 mm, width 440 mm, depth 131 mm, lamp power LED max. 45 W, lamp power NV/HV/TC max. 90 W, with support elements for housing stabilisation

Entry markings for electrical installation conduits (4 x up to 25 mm), flame-retardant in accordance with DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100



Assembly instructions



Planning data

Article number:	1293-00
E-No:	920839259
EAN:	4013456330214
Packaging quantity:	5

Dimensions / Form

Product length:	585 mm
Product width:	440 mm
Product depth:	131 mm

Assembly / Installation

Assembly type:	BB (solid construction)
----------------	-------------------------

Safety / Properties

Power consumption in housing LED:	45 W
-----------------------------------	------

KompaX® 1 housing system for fitted downlights and loudspeakers in concrete ceilings with wide range of accessories for almost all applications. Height-adjustable using intermediate frames. The various front parts make it extremely practical.

- Housing system for fitted downlights and loudspeakers
- For in-situ or prefabricated concrete
- For precise installation openings from Ø 160–300 mm
- For device installation depths up to 200 mm*
- For ceiling thicknesses from 180–300 mm*
- Tolerance compensation during slab ceiling installation