

Product datasheet:

KompaX®1 Front ring for ceiling exit Ø 215 mm

KompaX® 1 concrete installation housing

· Other dimensions and shapes (for ceiling exit) are available for fast delivery in the form of Styrofoam moulded parts.

Installation housing, KompaX® front ring for ceiling exit, installation diameter Ø 215 mm

Front part for concrete construction installation, on-site mixed concrete, fixing to formwork

Front ring made of plastic, for installation diameter Ø 215 mm, for luminaire coverings from Ø 222 mm, depth 14 mm, suitable for housing (1293-XX), flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100



Article number:	1293-71
EAN:	4013456331372
Packaging quantity:	10
Price group:	150

Dimensions / Form

Product depth:	14 mm
----------------	-------

Assembly / Installation

Assembly type:	BB (solid construction)
----------------	-------------------------

KompaX® 1 housing system for fitted downlights and loudspeakers in concrete ceilings with wide range of accessories for almost all applications. Height-adjustable using intermediate frames. The various front parts make it extremely practical.

- Housing system for fitted downlights and loudspeakers
- For in-situ or prefabricated concrete
- For precise installation openings from Ø 160–300 mm
- For device installation depths up to 200 mm*
- For ceiling thicknesses from 180–300 mm*
- Tolerance compensation during slab ceiling installation



Assembly instructions



Planning data