

Product datasheet:

KompaX®1 Front ring for ceiling exit (CE) in facing concrete version Ø 190 mm

KompaX® 1 concrete installation housing

- elastomer seal with flexible sealing edge
- prevents ingress of concrete, discolouring and sand blast dust
- for exact flush finishes in facing concrete without additional reworking

Installation housing, KompaX® front ring for ceiling exit, installation diameter Ø 190 mm, for facing concrete

Front part for concrete construction installation, on-site mixed concrete, fixing to formwork

Front ring made of plastic with elastomer seal, for installation diameter Ø 190 mm, for luminaire coverings from Ø 202 mm, depth 14 mm, suitable for housing (1293-XX), flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100



Article number:	1293-83
EAN:	4013456480681
Packaging quantity:	10
Price group:	150

Dimensions / Form

Product depth:	14 mm
----------------	-------

Assembly / Installation

Assembly type:	BB (solid construction)
----------------	-------------------------

KompaX® 1 housing system for fitted downlights and loudspeakers in concrete ceilings with wide range of accessories for almost all applications. Height-adjustable using intermediate frames. The various front parts make it extremely practical.

- Housing system for fitted downlights and loudspeakers
- For in-situ or prefabricated concrete
- For precise installation openings from Ø 160–300 mm
- For device installation depths up to 200 mm*
- For ceiling thicknesses from 180–300 mm*
- Tolerance compensation during slab ceiling installation



Assembly instructions



Planning data