

Product datasheet:

EnoX® luminaire and loudspeaker housing

EnoX® installation housing

- for installing luminaires, loudspeakers, displays and much more
- Minimum distance inside: min. 40 mm all round
- integrated stress relief (retention force) in accordance with DIN VDE 0606 / DIN EN 60670-1
- only for insulation material with heat resistance > 250 °C
- use only tested heat-resistant cables (N2 GMH 2G) and temperature-resistant terminals (e.g. T100)
- for installation devices up to LxW 120 x 220 mm or Ø 120 mm
- Heat distortion resistant to 220°C
- with 4 screws (FX⁴)



Article number:	9350-21
E-No:	920848309
EAN:	4013456532885
Packaging quantity:	10

Dimensions / Form

Product length:	368 mm
Product width:	268 mm
Product depth:	60 mm
Installation opening (for devices) width:	200 mm

Connections / Entries

For conduit Ø:	25 mm
----------------	-------

Assembly / Installation

Assembly type:	HW (drywall/lightweight construction)
----------------	---------------------------------------

Safety / Properties

Special application:	air-tight
----------------------	-----------



Assembly instructions



Planning data

EnoX® housing for luminaires and other devices in ceilings and walls which are produced in a lightweight design with an air-tight building shell. Variable installation space when there is insufficient room to install electrics in the insulation level.

- Air-tight installation in line with GEG energy-saving ordinance.
- No additional installation level is necessary
- For ceilings and walls in renovated and new buildings
- Toolless cable and conduit entry
- Thermally-protected installation space 300 x 200 x 55 mm
- ECON® technology for air-tight and toolless insertion
- FX⁴ technology for fast cavity wall installation