

Product datasheet:

ThermoX® housing for low and high-voltage luminaires

ThermoX® installation housing

- Suitable for halogen lamps and swivelling LED lamps.
- Maximum recessed depth: 65 mm for ZLS lamps, 70 mm for 230 V halogen lamps.
- Heat-resistant up to 220 °C.
- ZLS: maximum 35 W with aluminium reflector, 20 W Cool-Beam / ZLS: maximum 35 W with aluminium reflector (GU 10 base), 20 W Cool-Beam.
- Lamp power (230 V): maximum 35 W with aluminium reflector (GU 10 base).
- LED lamp power: maximum 6.6 W.
- Front panel can be used on both sides.

Installation housing, for hollow ceiling installation.

Installation housing, designed as an installation housing for front and rear installation in insulated hollow ceilings, made of plastic, for the installation of NV/HV halogen luminaires.

Front installation opening Ø 86 mm, rear installation opening Ø 74 mm, depth 90 mm, Luminaire installation diameter Ø 68 mm, luminaire installation height max. 65 mm (NV) / max. 70 mm (HV), for panel thickness 7-40 mm.

Lamp power max. 35 W with AL reflector
(not suitable for cold light lamps (Cool-Beam))



Planning data

Article number: **9300-01**

EAN: 4013456130814

Packaging quantity: 10

Dimensions / Form

Product depth: 90 mm

Installation opening (wall/ceiling) Ø: 74 mm

Assembly / Installation

Min. panel thickness: 7 mm

Panel thickness max.: 40 mm

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

Special application: Without

ETIM Product classification:

Built-in installation box luminaire

Suitable for high voltage luminaires: No

Suitable for low voltage luminaires: No

Suitable for LED luminaires: No

Suitable for lamp power: 35 W

Application: Hollow ceiling

With space for gear:

Built-in diameter: 120 mm

Product datasheet:

Built-in length:	
Built-in width:	
Built-in height/depth:	90 mm
Max. luminaire diameter:	120 mm
Min. ceiling thickness:	
Material:	Plastic

ThermoX® installation housing for installing halogen and pivoting recessed LED luminaires in various ceiling structures. The housing protects the surrounding material (moisture barrier foil, insulation etc.) from the lamp's extreme operating temperatures and creates an air-tight closure.

- Installation housing for halogen luminaires (low voltage and high voltage)
- Fire-preventive and air-tight
- For insulated hollow ceilings
- Two different front part types
- Integrated transformer closing cap
- Ceiling exits (CE) up to Ø 86 mm
- Installation from either above or below