

Product datasheet:

ThermoX® universal housing with mineral fibreboard

ThermoX® installation housing

- saves time - no plastering; close joint gap if necessary
- ceiling exit (CE) up to Ø 86 mm possible
- Heat-resistant up to 220 °C.
- Maximum recessed depth: 65 mm for ZLS lamps, 70 mm for 230 V halogen lamps.
- ZLS: maximum 35 W with aluminium reflector, 20 W Cool-Beam / ZLS: maximum 35 W with aluminium reflector (GU 10 base), 20 W Cool-Beam.
- lamp power for HV luminaires max. 35 W with AL reflector (base GU 10) /20 W Cool-Beam
- LED lamp power: maximum 6.6 W.



Article number:  **9300-22**

EAN: 4013456470347

Packaging quantity: 10

Dimensions / Form

Product depth: 90 mm

Installation opening (wall/ceiling) Ø: 120 mm

Assembly / Installation

Min. panel thickness: 7 mm

Panel thickness max.: 40 mm

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

Special application: Without

ETIM Product classification:

Built-in installation box luminaire

Suitable for high voltage luminaires: No

Suitable for low voltage luminaires: No

Suitable for LED luminaires: No

Suitable for lamp power: 35 W

Application: Hollow ceiling

With space for gear:

Built-in diameter: 120 mm

Built-in length:

Built-in width:

Built-in height/depth: 90 mm

Max. luminaire diameter: 120 mm

Min. ceiling thickness:



Planning data

Product datasheet:

Material:

Plastic

ThermoX® installation housing for installing halogen and pivoting recessed LED luminaires in various ceiling structures. The housing protects the surrounding material (moisture barrier foil, insulation etc.) from the lamp's extreme operating temperatures and creates an air-tight closure.

- Installation housing for halogen luminaires (low voltage and high voltage)
- Fire-preventive and air-tight
- For insulated hollow ceilings
- Two different front part types
- Integrated transformer closing cap
- Ceiling exits (CE) up to Ø 86 mm
- Installation from either above or below