

Product datasheet:

ThermoX® Decorative coverings

ThermoX® installation housing

- metal with galvanised or powder coating
- only for interiors
- minimum diameter of the luminaire 79 mm with ceiling exit Ø 68 and 75 mm
- Minimum diameter of luminaire covering 86 mm with ceiling exit Ø 82 mm

Decorative panel for ThermoX CE 82 mm, matt nickel (stainless steel look)



Article number:	9301-13
E-No:	920829319
EAN:	4013456212916
Inner packing / Packaging quantity:	1 / 10

Dimensions / Form

Product Ø:	125 mm
------------	--------

Assembly / Installation

Assembly type:	HW (drywall/lightweight construction)
----------------	---------------------------------------

Safety / Properties

Special application:	Without
----------------------	---------



Assembly instructions

ThermoX® installation housing for installing halogen and pivoting recessed LED luminaires in various ceiling structures. The housing protects the surrounding material (moisture barrier foil, insulation etc.) from the lamp's extreme operating temperatures and creates an air-tight closure.

- Installation housing for halogen luminaires (low voltage and high voltage)
- Fire-preventive and air-tight
- For insulated hollow ceilings
- Two different front part types
- Integrated transformer closing cap
- Ceiling exits (CE) up to Ø 86 mm
- Installation from either above or below