

## Product datasheet:

# ThermoX® LED housing

## Installation housing ThermoX® LED

- for rigid and pivoting LED luminaires
- circumferential airtight sealing lip
- Swivel trough for alignment of the luminaire

Installation housing, for hollow ceiling installation.

Installation housing, designed as an installation housing for front installation in insulated hollow ceilings, made of plastic, air-tight design in accordance with DIN 18015-5, for the installation of fixed and swivelling LED built-in luminaires.

Exit opening max. diameter 81 mm

(for square or rectangular cut-outs, diagonal max. 81 mm)

Light installation height max. 60 mm

Installation opening Ø 86 mm, depth 75 mm.

Lamp power max. 8 W



**Article number:**  **9320-20**

**EAN:** 4013456545762

**Packaging quantity:** 10

**Price group:** 160

### Dimensions / Form

**Product depth:** 75 mm

**Installation opening (wall/ceiling) Ø:** 81 mm

### Assembly / Installation

**Assembly type:** HW (drywall/lightweight construction)

### Safety / Properties

**Power consumption in housing LED:** 8 W

**Special application:** air-tight

ThermoX® LED installation housing for the airtight installation of rigid and pivoting LED built-in luminaires in different ceiling constructions. The housing protects the surrounding material (vapour barrier foil, insulation etc.) against the high operating temperatures and the LED luminaires themselves from contamination, and creates an airtight separation. In combination with the thermal separation between luminaire and operating device, in this way a maximum operating lifetime is obtained.

- For installation in insulated hollow ceilings
- Retrofitting from underneath
- Toolless installation of the housing
- Guarantees airtight installation
- Rear surface structure ensures optimal heat management
- Permanent and secure retention of the luminaire in the housing



Assembly instructions



Certificates



Planning data