


Product datasheet:

Installation housing AGRO ThermoX® Lite

Installation housing AGRO ThermoX® Lite

- Pre-drilled 20 mm and 25 mm pipe entries
- Tested with the most common LED spotlights
- For insulated or uninsulated false or suspended ceilings
- Building material class A2-s1, d0, can serve as preventive fire protection
- Fully closed installation housing despite conduit entries



Article number:  **9340-02**

E-No: 372912319

EAN: 7611614437255

Packaging quantity: 5

Dimensions / Form

Product length: 170 mm

Product width: 170 mm

Product depth: 65 mm

Installation opening (wall/ceiling) length: 135 mm

Installation opening (wall/ceiling) width: 135 mm

Installation opening (for devices) width: 140 mm

Cover for box/housing/casing Ø: 135x135 mm



Planning data

Assembly / Installation

Assembly type: HW (drywall/lightweight construction)

Wall thickness min.: 15 mm

Wall thickness max.: 15 mm

The new ThermoX® Lite product line is designed as a range of temperature-resistant housings for recessed lights. With its knock-in conduit entries, it is unique on the gypsum-fibre market. This range has been designed and tested for flexible installation of rigid and swivel luminaires with different mounting depths to ensure maximum durability.

- For installation in different ceiling constructions
- Knock-in conduit entries 20/25 mm
- For luminaires and fixtures of all types