

Product datasheet:

Fire-protection cover HWD 30-120

Ceiling box HWD 30

- For one-gang boxes/one-gang junction boxes and ceiling boxes HWD 90, HWD 30, HWD 68+, solid wood box PROTECT® and B15 PROTECT®
- Fire resistance class in accordance with ceiling or wall protection (F30-F120 and EI30-EI120)
- F30-F120 and EI30-EI120 function in conjunction with the one-gang box/one-gang junction box HWD 90
- F30 and EI30 function in conjunction with ceiling junction box HWD 30
- F30-F60 and EI30-EI60 function in connection with one-gang/one gang junction box HWD 68+



Article number:  **1184-94**

EAN: 4013456533431

Inner packing / Packaging quantity: 10 / 100

Price group: 192



Assembly / Installation

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

Halogen-free: Yes

Special application: Fire protection

Approvals / Certifications

fire resistance class: F 120

DIBT approval: Z-19.21-1788

VDE: Yes



Assembly instructions



Technical information



Planning data

HWD 30 ceiling box guarantees F30 (EI30) to F90 (EI90) fire protection. If a fire starts, the integrated fire-retardant coating immediately generates foam and seals the opening in the ceiling. Even when retrofitted, the HWD30 ceiling box provides protection.

- For F30-F90 or EI30-EI90 fire protection ceilings
- Encasing is not necessary
- For installation of smoke detectors, motion detectors, etc.
- With a fire-protection cover, can be used as a ceiling junction box
- Retrofitting also possible