

Product datasheet:

FlamoX® fire-protection putty

HWD 90 cavity wall boxes

- Building material forming an insulating layer
- for filling joints as well as bonding board materials
- Working time 30 mins.
- Can be stored up to 12 months
- Contents: 300 ml
- DIBt approval Z-19.11-1583

Article number:	9400-05
EAN:	4013456461611
Packaging quantity:	20
Price group:	191

Safety / Properties

Special application:	Fire protection
----------------------	-----------------

Approvals / Certifications

DIBT approval:	Z-19.11-1583
----------------	--------------

HWD 90 cavity wall boxes for F30-F120 or EI30-EI120 fire-protection walls ensure certified and fire-protection compliant electrical installation. They are also approved for timber walls in F30-B/F60-B timber frame or timber panel construction. No additional measures, such as encasing, are necessary. The intelligent AFS technology reacts immediately to fire and heat and automatically closes the installation opening. This guarantees the fire resistance class of the fire-protection wall and secures emergency routes. Use in all fire-protection walls and the fire-resistance duration of up to 120 minutes ensures maximum flexibility. At the same time, it also maintains the wall's sound insulation requirements.

- For F30-F120 or EI30-EI120 and F30-B / F60-B fire-protection walls
- Maintains the wall's sound insulation protection
- Retrofitting also possible
- With fire-protection cover, can be used as a junction box
- Also for directly opposing installation



Certificates



Technical information