

Product datasheet:

Quickbox® Maxi HWD 90 1x1

Fire protection cavity wall box

- Compatible with Feller SNAPFIX®
- for F30-F90 or EI30-EI90 fire-protection walls
- For timber stud walls F30-F90 or EI30-EI90
- VKF Approval 26831
- VKF Approval 26846
- for plate thickness > 10 - 40 mm
- matching plug-in cover for Art. No. 9498-77 New Look one Art. No. 9919.10
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm
- Pipes must be sealed with sealing plugs on both sides of the pipes!
- does not match with the following types:
- Prestige model by Feller Edizio Due



Article number:  **9499-77**

EAN: 7611614276786

Inner packing / Packaging quantity: 10 / 100

Price group: 192

Dimensions / Form

Product length: 83 mm

Product width: 83 mm

Product depth: 73.5 mm

Drill/cut hole Ø: 83 mm

Connections / Entries

For conduit Ø: 25 mm

Safety / Properties

Special application: Fire protection

Approvals / Certifications

fire resistance class: EI 90

HWD 90 cavity wall boxes for EI30-EI90 fire-protection walls ensure certified and fire-protection compliant electrical installation. Intelligent AFS technology reacts immediately to fire and heat and automatically seals the installation opening. This guarantees the fire resistance class of the fire-protection wall and secures escape routes. Use in all fire-protection walls and the fire-resistance duration of up to 90 minutes ensures maximum flexibility, even when the planning is changed. At the same time, it also maintains the wall's sound insulation requirements.

- Compatible with Feller SNAPFIX®
- For fire-protection walls F30-F90 or EI30-EI90
- For timber stud walls F30-F90 or EI30-EI90
- Maintains the wall's sound insulation protection
- Retrofitting also possible
- With fire-protection cover, can be used as a junction box
- May not be used inside encapsulated walls



Certificates



Technical information



Planning data