

Product datasheet:

Quickbox® Maxi HWD 90 2x2

Fire protection cavity wall box

- Compatible with Feller SNAPFIX®
- for F30-F90 or EI30-EI90 fire-protection walls
- For timber stud walls F30-F90 or EI30-EI90
- VKF Approval 26831
- VKF Approval 26846
- for plate thickness > 10 - 40 mm
- matching plug-in cover for Art. No. 9498-77 New Look one Art. No. 9919.10
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm
- Pipes must be sealed with sealing plugs on both sides of the pipes!
- does not match with the following types:
- Prestige model by Feller Edizio Due



Article number:	9499-77.02
E-No:	372632609
EAN:	7611614276793
Packaging quantity:	5

Dimensions / Form

Product length:	145 mm
Product width:	83 mm
Product depth:	73.5 mm
Drill/cut hole Ø:	83 mm

Connections / Entries

Number of entries:	2
For conduit Ø:	25 mm

Safety / Properties

Special application:	Fire protection
----------------------	-----------------

Approvals / Certifications

fire resistance class:	EI 90
------------------------	-------

HWD 90 cavity wall boxes for EI30-EI90 fire-protection walls ensure certified and fire-protection compliant electrical installation. Intelligent AFS technology reacts immediately to fire and heat and automatically seals the installation opening. This guarantees the fire resistance class of the fire-protection wall and secures escape routes. Use in all fire-protection walls and the fire-resistance duration of up to 90 minutes ensures maximum flexibility, even when the planning is changed. At the same time, it also maintains the wall's sound insulation requirements.

- Compatible with Feller SNAPFIX®
- For fire-protection walls F30-F90 or EI30-EI90
- For timber stud walls F30-F90 or EI30-EI90
- Maintains the wall's sound insulation protection
- Retrofitting also possible
- With fire-protection cover, can be used as a junction box
- May not be used inside encapsulated walls



Assembly instructions



Certificates



Planning data