

## Product datasheet:

# Quickbox® Maxi HWD 90 3x1

## Fire protection cavity wall box

- Compatible with Feller SNAPFIX®
- for F30-F90 or EI30-EI90 fire-protection walls
- For timber stud walls F30-F90 or EI30-EI90
- VKF Approval 26831
- VKF Approval 26846
- for plate thickness > 10 - 40 mm
- matching plug-in cover for Art. No. 9498-77 New Look one Art. No. 9919.10
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm
- Pipes must be sealed with sealing plugs on both sides of the pipes!
- does not match with the following types:
- Prestige model by Feller Edizio Due



|                        |               |
|------------------------|---------------|
| <b>Article number:</b> | 9499-77.03    |
| EAN:                   | 7611614276809 |
| Packaging quantity:    | 5             |
| Price group:           | 192           |

### Dimensions / Form

|                   |         |
|-------------------|---------|
| Product length:   | 205 mm  |
| Product width:    | 83 mm   |
| Product depth:    | 73.5 mm |
| Drill/cut hole Ø: | 83 mm   |

### Connections / Entries

|                    |       |
|--------------------|-------|
| Number of entries: | 2     |
| For conduit Ø:     | 25 mm |

### Safety / Properties

|                      |                 |
|----------------------|-----------------|
| Special application: | Fire protection |
|----------------------|-----------------|

### Approvals / Certifications

|                        |       |
|------------------------|-------|
| fire resistance class: | EI 90 |
|------------------------|-------|

HWD 90 cavity wall boxes for EI30-EI90 fire-protection walls ensure certified and fire-protection compliant electrical installation. Intelligent AFS technology reacts immediately to fire and heat and automatically seals the installation opening. This guarantees the fire resistance class of the fire-protection wall and secures escape routes. Use in all fire-protection walls and the fire-resistance duration of up to 90 minutes ensures maximum flexibility, even when the planning is changed. At the same time, it also maintains the wall's sound insulation requirements.

- Compatible with Feller SNAPFIX®
- For fire-protection walls F30-F90 or EI30-EI90
- For timber stud walls F30-F90 or EI30-EI90
- Maintains the wall's sound insulation protection
- Retrofitting also possible
- With fire-protection cover, can be used as a junction box
- May not be used inside encapsulated walls



Certificates



Technical information



Planning data