

# Product datasheet:

## New Record

- Applicable in hollow ceiling constructions.
- Suitable for rachel ceilings and metal stud ceilings.
- Connectors from Wago-Winsta RD
- Equipped with 1x power supply (male black), 1x switch (female brown), 1x light point forwarding (female white), 1x light point on central box cover.



**Article number:** **➔ AT1307**

**EAN:** 8712259343426

### Dimensions / Form

Product Ø: 79 mm

Installation opening (wall/ceiling) Ø: 76 mm

### Connections / Entries

Number of entries: 12

For conduit Ø: 19 mm

### Electrical Properties

Number of outputs: 4

Circuit: 1-pole 2-fold

### ETIM Product classification:

#### Box/housing for built-in mounting in the wall/ceiling

Mounting method: Hollow ceiling

Shape: Round

Construction type: Central conduit box

Model: Single

Provided with revolving ring: No

Couplable: No

Equipped with: Other

Diameter: 76 mm

Length:

Width:

Depth:

Inner depth: 77 mm

Suitable for wall/board thickness:

Suitable for number of device inserts: 0

Mounting switching equipment:

With screws: No

Number of non-adjustable device fixing lugs:

Number of adjustable device fixing lugs:

## Product datasheet:

|                                            |                     |
|--------------------------------------------|---------------------|
| Housing feed-through by break-out opening: | No                  |
| Housing feed-through by seal membrane:     | No                  |
| Housing feed-through by nozzle:            | No                  |
| Housing feed-through by step membrane:     | No                  |
| Suitable for tube diameter:                | 16/19 mm            |
| Suitable for cable diameter:               |                     |
| Pipe locking:                              | No                  |
| Pipe locking optional:                     | No                  |
| Inlet from the rear:                       | No                  |
| Number of inlets:                          | 12                  |
| Number of included spouts:                 | 0                   |
| Material:                                  | Plastic             |
| Halogen free:                              | No                  |
| Surface protection:                        | Untreated           |
| Colour:                                    | Grey                |
| Degree of protection (IP):                 | IP20                |
| Degree of protection (NEMA):               |                     |
| Cover model:                               | Mounting cover      |
| Transparent cover:                         | No                  |
| Cover attachment:                          | Screwed             |
| Sealable:                                  | No                  |
| Circuit integrity:                         | None                |
| With screening:                            | No                  |
| Airtight:                                  | No                  |
| Max. conductor cross section:              | 2,5 mm <sup>2</sup> |
| Number of poles of the clamp:              | 0                   |
| Clamp position fixed:                      | No                  |
| Luminaire hook mounting:                   | No                  |
| Nozzle:                                    | Tunnel branch pipe  |
| Special application:                       | Other               |
| With partition panel:                      |                     |
| Compliant with BS 4662:                    |                     |