

## Product datasheet:

- Equipped with 1x power supply (male black), 1x switch (female brown), 1x light point connection (female white).

**Article number:** **↻ AT3310**

**EAN:** 8712259362885

### Connections / Entries

**Number of entries:** 10

### Electrical Properties

**Circuit:** 1-pole



### ETIM Product classification:

#### Box/housing for surface mounting on the wall/ceiling

**Model:**

**Equipped with:** Mounting plate

**Max. conductor cross section:** 6 mm<sup>2</sup>

**Number of poles:**

**Number of clamp positions per pole:**

**Shape:** Rectangular

**Mounting method:** Wall-/ceiling mounting

**Mounting in the soil:** No

**Mounting under water:** No

**Suitable for tube diameter:** Other

**Number of inlets:** 10

**Inlet from the rear:** No

**Length:** 120 mm

**Width:** 95 mm

**Depth:** 60 mm

**Diameter:**

**Number of cable glands included:**

**Connectable:** No

**Type of housing feed-through:** None

**With strain relief:**

**Material:** Plastic

**Halogen free:** No

**Surface protection:** Untreated

**Colour:** Grey

**RAL-number (similar):**

**Degree of protection (IP):** IP40

**Degree of protection (NEMA):**

## Product datasheet:

|                                                                         |             |
|-------------------------------------------------------------------------|-------------|
| Cover model:                                                            | Blind cover |
| Outgoing connections with connectors for plug-in building installation: |             |
| Transparent cover:                                                      | No          |
| Castable:                                                               | No          |
| Cover attachment:                                                       | Snapped on  |
| Casting compound included:                                              | No          |
| Sealable:                                                               | No          |
| Rated insulation voltage Ui:                                            | 690 V       |
| Circuit integrity:                                                      | None        |
| With screening:                                                         | No          |
| Weatherproof:                                                           | No          |
| Working temperature:                                                    | -40 - 70 °C |
| Explosion-tested version:                                               | No          |
| Suitable for Ex-zone gas:                                               | None        |
| Suitable for Ex-zone dust:                                              | None        |