

Product datasheet:

- Equipped with 1x power supply (male black), 1x switch (female brown), 1x light point connection (female white).

Article number:  **AT3313**

EAN: 8712259362915

Connections / Entries

Number of entries: 10

Electrical Properties

Number of outputs: 3

Circuit: 1-pole

ETIM Product classification:

Box/housing for surface mounting on the wall/ceiling

Model:

Equipped with: Mounting plate

Max. conductor cross section: 6 mm²

Number of poles:

Number of clamp positions per pole:

Shape: Rectangular

Mounting method: Wall-/ceiling mounting

Mounting in the soil: No

Mounting under water: No

Suitable for tube diameter: Other

Number of inlets: 10

Inlet from the rear: No

Length: 120 mm

Width: 95 mm

Depth: 60 mm

Diameter:

Number of cable glands included:

Connectable: No

Type of housing feed-through: None

With strain relief:

Material: Plastic

Halogen free: No

Surface protection: Untreated

Colour: Grey

RAL-number (similar):

Degree of protection (IP): IP40



Product datasheet:

Degree of protection (NEMA):

Cover model:	Blind cover
Outgoing connections with connectors for plug-in building installation:	
Transparent cover:	No
Castable:	No
Cover attachment:	Snapped on
Casting compound included:	No
Sealable:	No
Rated insulation voltage Ui:	690 V
Circuit integrity:	None
With screening:	No
Weatherproof:	No
Working temperature:	-40 - 70 °C
Explosion-tested version:	No
Suitable for Ex-zone gas:	None
Suitable for Ex-zone dust:	None