

Product datasheet:

· Equipped with 1x power supply (male black), 1x switch (female brown), 1x light point connection (female white).

Article number:  **AT3314**

EAN: 8712259362922

Connections / Entries

Number of entries: 10

Electrical Properties

Number of outputs: 4

Circuit: 1-pole

ETIM Product classification:

Box/housing for surface mounting on the wall/ceiling

Model:

Equipped with: Mounting plate

Max. conductor cross section: 6 mm²

Number of poles:

Number of clamp positions per pole:

Shape: Rectangular

Mounting method: Wall-/ceiling mounting

Mounting in the soil: No

Mounting under water: No

Suitable for tube diameter: Other

Number of inlets: 10

Inlet from the rear: No

Length: 120 mm

Width: 95 mm

Depth: 60 mm

Diameter:

Number of cable glands included:

Connectable: No

Type of housing feed-through: None

With strain relief:

Material: Plastic

Halogen free: No

Surface protection: Untreated

Colour: Grey

RAL-number (similar):

Degree of protection (IP): IP40



Product datasheet:

Degree of protection (NEMA):

Cover model:	Blind cover
--------------	-------------

Outgoing connections with connectors for
plug-in building installation:

Transparent cover:	No
--------------------	----

Castable:	No
-----------	----

Cover attachment:	Snapped on
-------------------	------------

Casting compound included:	No
----------------------------	----

Sealable:	No
-----------	----

Rated insulation voltage Ui:	690 V
------------------------------	-------

Circuit integrity:	None
--------------------	------

With screening:	No
-----------------	----

Weatherproof:	No
---------------	----

Working temperature:	-40 - 70 °C
----------------------	-------------

Explosion-tested version:	No
---------------------------	----

Suitable for Ex-zone gas:	None
---------------------------	------

Suitable for Ex-zone dust:	None
----------------------------	------