

Product datasheet:

NXT MAW-23/23/00-H2 Distribution board

Installation 2.0 Click-mate NXT distribution boards

Article number:  **AT91622**

EAN: 8712259559643

Dimensions / Form

Product width: 220 mm

Product depth: 390 mm

Electrical Properties

Rated current: 40 A

Number of residual current circuit breakers 2P: 2

Total number of circuit breakers: 6

Main switch (xxA): 40 A

Connection (1/3-phase): 1-phase

Grey groups: 3

ETIM Product classification: Small distribution board equipped

Mounting method: Surface mounted

Number of rows:

Number of phases: 1

Protection: Miniature-/earth leakage circuit breaker

Number of single-phase miniature circuit breakers (MCB):

Number of three-phase miniature circuit breakers (MCB):

Release characteristic:

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 230 V:

Power consumption:

Total number of groups: 6

Number of direct groups: 0

Number of light groups: 6

Number of groups behind earth leakage switch: 6

Number of earth leakage circuit breakers: 0

Number of earth leakage switches 30 mA: 2

Number of earth leakage switches 300 mA: 0



Product datasheet:

Number of arc fault detection devices

AFDD:

Number of earth leakage circuit breakers/

AFDD:

Protection main switch:

Number of poles main switch:

2

Main switch rated current:

40 A

Protection incoming RCD:

Protection high integrity:

Protection split load:

Protection dual RCD:

Number of outgoing ways:

Suitable for data:

Cooker group:

None

Cooker group suitable as power current
group:

With socket outlet:

No

With bell transformer:

No

Overvoltage protection:

No

Type of overvoltage protection device:

Outgoing connections with connectors for
plug-in building installation:

With meter:

With N-disconnect slide:

Connection type:

Housing material:

Plastic

Degree of protection (IP):

IP2XC

Height:

390 mm

Built-in height:

Width:

220 mm

Built-in width:

Width in number of modular spacings:

24

Depth:

110 mm

Built-in depth:

Extension possible:

No

Type of covering:

With transparent cover:

No

Type of closure:

Lockable:

No

Colour:

RAL-number:

Product datasheet:

Especially for the Installation 2.0 concept, Attema has extended its range of Click-mate NXT distribution boards with a pluggable output bridge. The fully pre-wired pluggable output bridge can be fitted with up to 12 to 16 connections for single-phase end groups. Connections for electric cooking, mechanical ventilation or power groups have also been taken into account: space is reserved in the output bridge for up to 2 to 4 pieces of 5-pin flat connectors. All connectors are pre-wired with 2.5 mm² and equipped with locking latches as standard.

Almost all "traditional" distribution boards can be equipped with a fully pre-wired output bridge with round connectors. Just like the standard distribution boards, Attema assembles the pluggable distribution boards completely as desired within a few days.

Looking for a different configuration? Use the Click-mate NXT Assistant tool to assemble your own pluggable distribution box in no time. Or ask one of our sales staff about the possibilities.