

Product datasheet:

NXT MAW-23/23/22F-H4 Distribution board

Installation 2.0 Click-mate NXT distribution boards

Article number:  **AT91627**

EAN: 8712259559698

Dimensions / Form

Product width: 220 mm

Product depth: 390 mm

Electrical Properties

Rated current: 3x32 A

Number of residual current circuit breakers 2P: 3

Total number of circuit breakers: 9

Main switch (xxA): 40 A

Connection (1/3-phase): 3-phase

Light blue groups: 3

Grey groups: 3

Cooker group (1/3-phase): 3-phase

ETIM Product classification: Small distribution board equipped

Mounting method: Surface mounted

Number of rows:

Number of phases: 3

Protection: Miniature-/earth leakage circuit breaker

Number of single-phase miniature circuit breakers (MCB):

Number of three-phase miniature circuit breakers (MCB):

Release characteristic:

Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V:

Power consumption:

Total number of groups: 9


Number of direct groups: 0

Number of light groups: 8

Number of groups behind earth leakage switch: 8

Number of earth leakage circuit breakers: 0

Number of earth leakage switches 30 mA: 3



Product datasheet:

Number of earth leakage switches 300 mA:	0
Number of arc fault detection devices AFDD:	
Number of earth leakage circuit breakers/ AFDD:	
Protection main switch:	
Number of poles main switch:	4
Main switch rated current:	40 A
Protection incoming RCD:	
Protection high integrity:	
Protection split load:	
Protection dual RCD:	
Number of outgoing ways:	
Suitable for data:	
Cooker group:	Single phase
Cooker group suitable as power current group:	No
With socket outlet:	No
With bell transformer:	No
Overvoltage protection:	No
Type of overvoltage protection device:	
Outgoing connections with connectors for plug-in building installation:	
With meter:	
With N-disconnect slide:	
Connection type:	
Housing material:	Plastic
Degree of protection (IP):	IP2XC
Height:	390 mm
Built-in height:	
Width:	220 mm
Built-in width:	
Width in number of modular spacings:	24
Depth:	110 mm
Built-in depth:	
Extension possible:	No
Type of covering:	
With transparent cover:	No
Type of closure:	
Lockable:	No
Colour:	

Product datasheet:

RAL-number:

Especially for the Installation 2.0 concept, Attema has extended its range of Click-mate NXT distribution boards with a pluggable output bridge. The fully pre-wired pluggable output bridge can be fitted with up to 12 to 16 connections for single-phase end groups. Connections for electric cooking, mechanical ventilation or power groups have also been taken into account: space is reserved in the output bridge for up to 2 to 4 pieces of 5-pin flat connectors. All connectors are pre-wired with 2.5 mm² and equipped with locking latches as standard.

Almost all "traditional" distribution boards can be equipped with a fully pre-wired output bridge with round connectors. Just like the standard distribution boards, Attema assembles the pluggable distribution boards completely as desired within a few days.

Looking for a different configuration? Use the Click-mate NXT Assistant tool to assemble your own pluggable distribution box in no time. Or ask one of our sales staff about the possibilities.