Product datasheet:

Installation 2.0 Cables

· Suitable for use in hollow spaces
· Maintenance-free according to EN-IEC 61535
· Equipped with Attema connectors



Article number:	**AT8330.07**
EAN:	8712259597256
Packaging quantity:	10

Dimensions / Form

Cable length:	7 m

Electrical Properties

Cable/electric cable Ø:	9.7 mm

Approvals / Certifications

Fire class:	ECA

ETIM Product classification:
Patch cord for plug-in building installation

Rated voltage:	400 V
Rated current:	16 A
Number of poles:	3
Degree of protection (IP):	IP20
Type of finished cable:	Power cord
Type side 1:	Bus
Type side 2:	Free conductor end
Conductor end treatment:	Ultrasonic compressed wire ends
Total length:	7.000 mm
Mechanical coding:	No
Colour coding/contact insert:	Black
RAL-number coding/contact insert:	
Housing material:	
Housing colour:	Black
Cable type:	H05VV-F
Cable diameter:	97 mm
Dismantle length:	90 mm
Strip length:	12 mm
Colour outer sheath:	Black
Pole codification:	L, N, PE
Nominal cross section conductor:	2,5 mm²
Type of locking:	Integrated in plug-in connector

Product datasheet:

Insulating piece permanent temperature-resistant:	90 °C
Cable permanent temperature-resistant to:	60 °C
Max. operating temperature at conductor:	50 °C
Halogen free:	No
Fire load:	3,01 kWh
Contact material:	
Surface coating contacts:	Tinned
Pollution degree:	2
Continuity resistance:	0 mOhm
Rated surge voltage:	4 kV
Reaction-to-fire according to EN 13501-6: Class:	
Reaction-to-fire according to EN 13501-6: Smoke production:	
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles:	
Reaction-to-fire according to EN 13501-6: Acidity:	

Installation 2.0 is a pluggable installation system based on pre-wired central and cable boxes in combination with prefabricated mounted switching material and a pluggable group box. These components are connected with flexible cables. The installation time is therefore greatly reduced compared to traditional installation, and failure costs are kept to a minimum.

Cca cords
Fire class Cca cords are available upon request. Contact us for current delivery times.