

## Product datasheet:

- Applicable in hollow ceiling constructions.
- Suitable for rachel ceilings and metal stud ceilings.

**Article number:**  **AT8419-3**

**EAN:** 8712259604527

### Dimensions / Form

**Product Ø:** 79 mm

**Installation opening (wall/ceiling) Ø:** 76 mm

### Connections / Entries

**Number of entries:** 12

**For conduit Ø:** 19 mm

### Assembly / Installation

**Assembly type:** hollow ceiling

### Safety / Properties

**Special application:** Without

### Electrical Properties

**Number of outputs:** 3

### ETIM Product classification:

#### Box/housing for built-in mounting in the wall/ceiling

**Mounting method:** Hollow ceiling

**Shape:** Round

**Construction type:** Central conduit box

**Model:** Single

**Provided with revolving ring:** No

**Couplable:** No

**Equipped with:** Other

**Diameter:** 76 mm

**Length:**

**Width:**

**Depth:** 79 mm

**Inner depth:** 77 mm

**Suitable for wall/board thickness:**

**Suitable for number of device inserts:**

**Mounting switching equipment:**

**With screws:** No

**Number of non-adjustable device fixing lugs:**



## Product datasheet:

Number of adjustable device fixing lugs:

|                                            |                     |
|--------------------------------------------|---------------------|
| Housing feed-through by break-out opening: | No                  |
| Housing feed-through by seal membrane:     | No                  |
| Housing feed-through by nozzle:            | No                  |
| Housing feed-through by step membrane:     | No                  |
| Suitable for tube diameter:                | 16/19 mm            |
| Suitable for cable diameter:               |                     |
| Pipe locking:                              | No                  |
| Pipe locking optional:                     | No                  |
| Inlet from the rear:                       | No                  |
| Number of inlets:                          | 12                  |
| Number of included spouts:                 | 0                   |
| Material:                                  | Plastic             |
| Halogen free:                              | No                  |
| Surface protection:                        |                     |
| Colour:                                    | Grey                |
| Degree of protection (IP):                 |                     |
| Degree of protection (NEMA):               |                     |
| Cover model:                               | Mounting cover      |
| Transparent cover:                         | No                  |
| Cover attachment:                          | Screwed             |
| Sealable:                                  | No                  |
| Circuit integrity:                         | None                |
| With screening:                            | No                  |
| Airtight:                                  | No                  |
| Max. conductor cross section:              | 2,5 mm <sup>2</sup> |
| Number of poles of the clamp:              | 0                   |
| Clamp position fixed:                      | No                  |
| Luminaire hook mounting:                   | No                  |
| Nozzle:                                    | Tunnel branch pipe  |
| Special application:                       | Other               |
| With partition panel:                      |                     |
| Compliant with BS 4662:                    |                     |